

# 3M™ Digital Wall Display

## 9200IW Plus

For trainers and presenters who need to ensure their message is understood and remembered. The 3M Digital Wall Display Plus Series combines: state of the art projection, digital annotation and mouse control, in a remarkably easy, wall mounted design to maximize communication in the most demanding settings. The multiple tools integrated into Digital Wall Display Plus make it ideal for capturing and communicating vast and complicated quantities of information.



Order Number: 78-9236-6842-6

Integrated Projector | Erasable Write-On Screen | Powerful Speakers

|                            |  |
|----------------------------|--|
| <b>Display Screen</b>      | 60" diagonal, easy erase screen surface; 4:3 aspect ratio; 48" W x 36" H       |
| <b>Viewing Angle</b>       | 170° horizontal, 170° vertical   |
| <b>Optical Structure</b>   | Single 0.7" , DLP™ Texas Instruments Incorporated technology, XGA (1024 x 768) |
| <b>Keystone Adjustment</b> | Optically corrected, electronic for fine adjustments                           |
| <b>Throw Ratio</b>         | Distance/Diagonal: 755 mm/ 1524 mm = .5  |
| <b>Colors</b>              | 24 bit full color  |
| <b>Contrast Ratio</b>      | 300:1 typical; 200:1 minimum   |
| <b>Lamp Type</b>           | VIP 250W   |
| Lamp Life                  | 1600 Hours typical   |
| <b>Dimensions</b>          | 47.6" H x 53.2"W x 7.0"D (1208 mm x 1350 mm x 179 mm)                          |
| Wall-to-screen             | 7.05" (18cm) including mounting bracket  |
| <b>Weight</b>              | Approx. 85 lbs. (39 kg.)   |
| <b>Video Compatibility</b> | NTSC, PAL, SECAM, 720P   |
| <b>RGB Compatibility</b>   | VGA to SXGA; 640 x 480, 800 x 600, 1024 x 768, 1280 x 1024 (1600 x 1200 DVI-D) |
| <b>Mouse Emulation</b>     | USB  |
| <b>Computer Input</b>      | VGA, DVI-I (DVI-D + DVI-A)   |
| <b>Video Input</b>         | Component, S-video, Composite  |
| <b>Audio in</b>            | 2 RCA jacks, 2 x 3.5 mm stereo mini jack                                       |
| <b>Audio out</b>           | RCA jacks loop-through (with delay adjustment)                                 |
| <b>Serial Control</b>      | 9 pin D-Sub, RS-232, Ethernet Connector  |
| <b>Audio amp</b>           | 20 Watts per channel   |
| Speakers                   | 2 x 20W stereo 8 Ω   |
| <b>Power Requirements</b>  | Input 100-240 VAC, 50/60 Hz, 3 Wire Grounded, 355 W. max                       |
| <b>Environmental</b>       |  |
| Operating                  | 10 - 35°C, 10 - 85%RH, without condensation                                    |
| Storage                    | -10 - 60°C, 10 - 85%RH, without condensation                                   |
| Altitude                   | 0 - 6000 feet above sea level  |
| <b>Regulatory</b>          | UL, CE, FCC Class A, CISPR Class A   |
| <b>Menu System</b>         | On-screen menu system; operable with or without remote                         |
| <b>Presentation Tools</b>  | Reveal, Blank, Pointer, and Timer  |
| <b>Warranty</b>            | One-year limited warranty on parts and labor; 90 day warranty on lamp          |

## INTERACTIVE WHITEBOARD:

### Features:

- Capture notes in color and save or send them in various file formats instantly (JPEG, GIF, TIFF, HTML, PDF, vector PDF, EPS, BMP 256 color, BMP monochrome, WBD) Powerpoint® (ppt & pps) and metafile (wmf)
- Interactive Display- control computer mouse functions with the digital presentation pen
- Annotate and edit text and drawings on-line from remote locations
- Microsoft® NetMeeting® compatible
- Playback feature allows you to review all drawings on the board including erased items
- Import files from most business programs. annotate and save changes. (PPT, BMP, GIF, JPEG, ICO, EMF, WMF, Microsoft® Excel®, Clipboard files) Microsoft® Word® (doc & rtf)
- PC and Macintosh® compatible
- On screen keyboard

### Minimum System Requirements:

#### PC

- Microsoft® Windows® compatible computer with Pentium II® 400 Mhz processor
- Windows 98, 2000, ME, XP and Windows NT 4.0 compatible (other platform users may view shared meetings via Java applet through Java-enabled browser)
- 10 MB available hard drive space
- CD-ROM drive or Internet connection for software installation
- One available serial port or USB port (USB Serial Adapter required)

#### MAC

- Power Macintosh®
- Mac OS® 9.x with Macintosh Runtime for Java™ 2.2 or higher and 64 MB RAM, or Mac OS X 10.1 or higher
- 10 MB available hard drive space
- One available USB port (USB Serial Adapter required)

## WHITEBOARD ACCESSORIES INCLUDE:

- (1) 3M™ Cleaning Cloth
- (1) software cd
- (1) digital presentation pen
- (1) AA battery

### Replacement Batteries:

- Presentation Pen (1) AA battery

## OPTIONAL ACCESSORIES:

- |   |                |
|---|----------------|
| • Adjustable height mobile cart                   | 78-6969-9752-3 |
| • Mobile Cart Glass Tray                          | 78-6969-9783-8 |
| • Accessory tray (left)                           | 78-6969-9754-9 |
| • Accessory Tray (right)                          | 78-6969-9753-1 |
| • 1 year extended warranty (includes 1 free lamp) | 78-6969-9596-4 |
| • Installation service                            | 78-6969-3269-0 |
| • Spare lamp (9000 series)                        | 78-6969-9736-6 |
| • Digital Presentation pen                        | 78-6969-9777-0 |



1-800-328-1371

[www.3m.com/meetings](http://www.3m.com/meetings)

### Important Notice

All statements, technical information, and recommendations related to 3M's products are on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publication, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

### Warranty; Limited Remedy; Limited Liability

This product will be free from defects in material and manufacture for a period of one year from the date of purchase. 3M MAKES NO OTHER WARRANTIES or CONDITIONS INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.

Specifications subject to change without notice.

3M is a trademark of 3M Company. Used under license in Canada. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

**3M Visual Systems**  
Building A 147-5N-01  
6801 River Place Blvd.  
Austin, TX 78726-9000

**3M Mexico, S. A. de C. V.**  
Apartado Postal 14-139  
Mexico, D. F. 07070  
Mexico

**3M Canada**  
P. O. Box 5757  
London, Ontario,  
Canada  
N6A 4T1

©3M 2005 121405  
78-6970-8600-3

